

Support de parquet / Manufacture



MASSIF SOLID

9 x 64/68 et 84/88 mm



SEMI-MASSIF ENGINEERED WOOD FLOORING

11 x 86 mm et 15 x 136 mm

Pose collée impérative pour le massif et le Loft Pro
Full glued installation compulsory for solid and engineered wood flooring

MASSIF / SOLID							CHAUFFAGE AU SOL / UNDERFLOOR HEATING	
ESSENCE / SPECIE	SECTION / SIZE	LONG. / LENGTH	PROFIL / PROFILE	FINITION / FINISH	USINAGE / MANUFACTURING	COLISAGE / PACKAGE	UNDERFLOOR HEATING	
TECK / TEAK	9 x 64/68	300-1200	R + L* T + G*	Pré-huilé Pre-Oiled	Joint intégré noir Integrated black joint	1 m ²		
TECK / TEAK	9 x 84/88	300-1200				1 m ²		
PAREMENT 3,5 MM / TOP LAYER 3,5 MM								
ACACIA	11 x 86	300-1200	R + L* T + G*	Pré-huilé Pre-Oiled	Joint intégré noir Integrated black joint	1 m ²		
DOUSSIE	11 x 86	300-1200				1 m ²		
IROKO	11 x 86	300-1200				1 m ²		
WENGÉ	11 x 86	300-1200				1 m ²		
TECK / TEAK	15 x 136	500-1800				1,224 m ²		

*R+L : rainure et languette / T+G : Tongue and groove



Parquet compatible avec sol chauffant/rafraîchissant en pose collée. Pose collée avec colle PS fortement conseillée pour une meilleure conductivité thermique.
Compatible parquet on underfloor heating /refreshing heating floor with glued laying. Glued laying with PS glue, strongly advised for better thermal conductivity.